




















OSCAR SUPER SEMI GLOSS 5766

Product Description	A superior quality emulsion semi gloss paint made of Pure Acrylic Emulsion. It is mainly designed for exterior application. It provides excellent semi gloss finish on the wall. It shows low dirt pick up compare with acrylic copolymer based emulsion paints. It gives more durability and good weather resistance.	 Interior/Exterior
Recommended Uses	- This product is designed for decoration of exterior surfaces. It also can apply on interior surfaces.	 Water Based
Substrate	-Cement plaster, concrete, block work, rendered surfaces, gypsum board etc. Substrate should be sound and any defects in the substrate like surface undulations, cracks, pin holes etc. should be rectified/filled before starting the painting.	 Volume Solid 40 ± 2%
Special Features	<ul style="list-style-type: none"> • Excellent dirt pick up resistance • Good weather stability & weather resistance • Tough and durable film protects the surface • Formaldehyde free, Low VOC Product • Good flow & leveling and easy to apply • Excellent spreading on substrate 	 Coverage: 9.7-13 m2/L
Product test standards	<p>Specific Gravity:</p> <p>ASTM D 1475 / BS EN ISO 2811-1 : 2016</p> <p>Gloss:</p> <p>ASTM D 523 / BS EN ISO 2813 : 2014</p> <p>Volume Solids:</p> <p>ASTM D 2697 / BS EN ISO 3233-3 : 2015</p> <p>Viscosity:</p> <p>ASTM D 562</p>	 Roller  Brush  Spray Gun
Packing	18 LTR 3.75 LTR 1 LTR	

Storage	Store in cool and well ventilated place protected from heat and direct sunlight. Containers must be kept tightly closed.	 VOC < 50 g/L
Flash Point	Not Applicable	
Physical Properties		Surface Drying: 1 Hour.@ 30° C
Finish	Smooth-Semi-Gloss	
Color	White and as per Oscar Color card	
Specific Gravity	1.24+/-0.02	
Volume Solids	40 ± 2 %	
Thinner & Cleaner	Water	
Mixing Ratio	Not Applicable	
Pot Life	Not Applicable	
Shelf Life	24 month when stored in original sealed container In a cool dry place	 Hard Drying: 24 hours @ 30° C
Wet Film Thickness	77-103 μ	
Dry Film Thickness	30-40 μ per each coat	
Theoretical Coverage	9.7-13 m ² /L per each coat	 3.75 L
	Spreading rate depends on applied film thickness, surface imperfections, type of surface texture, porosity of the substrate, environment temperature and wastage during application. Maximum spread rate per coat is obtained at minimum dry film thickness and vice versa.	
Surface Dry	Approximately 1 hour at 30° C	
Hard dry	24 hours at 30° C	 18 L
Surface Preparation	The surface to be coated should be clean, non-chalky, dry and free from loose material, dust etc. In case of need sanding required to remove loose particles from the surface.	
Recommended Coating System	Stir the contents well before use. Do not apply the paint in very cold conditions, to impervious surfaces or surfaces subject to steam and condensation. It is advisable to build up coat thickness by applying in thin layers, instead of applying one single thick coat to avoid cracking. Avoid painting below 10° C and humidity more than 85% .	 Non-Flammable

<u>Exterior</u> Primer Mid Coat Top Coat	1 X Oscar Original Sealer 5290 2 X Oscar Beauty Putty 5510 2 X Oscar Super Beauty Semi-Gloss 5766	 Paint System
<u>Interior</u> Primer Mid Coat Top Coat	1 X Oscar Beauty Sealer 5292 2 X Oscar Beauty Putty 5510 2 X Oscar Super Beauty Semi-Gloss 5766	
<u>Repainting System</u> Substrate Primer Top Coat	Any smooth/textured existing surfaces 1 X Oscar Original Sealer 5290 2 X Oscar Super Beauty Semi-Gloss 5766	 Splashes on eye-wash with Water
<u>Application Data</u>	Guidelines for Airless Spray Application Nozzile Orifice : 0.021" - 0.027" Spray Angle : 65° -80° Nozzile Pressure : 140-190 kg/cm2 (2100psi)	
Health and Safety	<p>Ensure good ventilation during application and drying.</p> <p>Avoid contact of the product with skin and eyes by using proper gloves, apron , goggles and mask.</p> <p>If splashes enter eyes wash with plenty of water.</p> <p>Keep out of reach of children.</p> <p>Remove splashes from skin with soap and warm water.</p> <p>In case of insufficient ventilation during spraying, wear suitable respiratory equipment.</p> <p>Do not breathe vapour / spray.</p>	 Splashes on Skin-wash with soap & hot water
DISCLAIMER	<p>The above information is based on internal testing and our accumulated experience. This information is given in good faith but without warranty as the conditions under which the product is used are often beyond our control. This data sheet supersedes those previously issued and may be changed without prior notice.</p>	 Disclaimer

