


















## OSCAR AL ATIQUE 5355

<b>Product Description</b>	High Quality Texture paint made of co-polymer emulsion. It can be used for interior and exterior application. It shows better weather stability. It gives antique finish. The appearance of the finish is like olden days houses made of mud, like a heritage villa. The application is by trowel and hand, it is easy to apply.	 Interior/Exterior
<b>Recommended Uses</b>	- This product is designed for decoration of interior and exterior surfaces.	 Water Based
<b>Substrate</b>	-Cement plaster, concrete, block work, rendered surfaces, gypsum board etc. Substrate should be sound and any defects in the substrate like surface undulations, cracks, pin holes etc. should be rectified/filled before starting the painting.	 Volume Solid 57 ± 2%
<b>Special Features</b>	<ul style="list-style-type: none"> <li>• Antique finish</li> <li>• Rough textured finish</li> <li>• Better coverage and spread rate</li> <li>• Easy to apply</li> <li>• Identical finish (hay mix)</li> <li>• Better adhesion on wall substrate</li> </ul>	 Coverage: 0.5-1.0 m2/L
<b>Product test standards</b>	<p><i>Specific Gravity:</i></p> <p>ASTM D 1475 / BS EN ISO 2811-1 : 2016</p> <p><i>Gloss:</i></p> <p>ASTM D 523 / BS EN ISO 2813 : 2014</p> <p><i>Volume Solids:</i></p> <p>ASTM D 2697 / BS EN ISO 3233-3 : 2015</p> <p><i>Viscosity:</i></p> <p>ASTM D 562</p>	 Trowel
<b>Packing</b>	25 KG	 Gloves

<b>Storage</b>	Store in cool and well ventilated place protected from heat and direct sunlight. Containers must be kept tightly closed.	 VOC -7 g/L
<b>Flash Point</b>	Not Applicable	
<b>Physical Properties</b>		Surface Drying: 1 Hours @30°C
Finish	Texture-Matt	
Colors	Beige Color	
Specific Gravity	1.70+/-0.02	
Volume Solids	57 ± 2 % ; approximately 75 ± 2% by Weight	
Thinner & Cleaner	Water	
Dilution	0-5% Water	
Mixing Ratio	Not Applicable	
Pot Life	Not Applicable	
Shelf Life	24 month when stored in original sealed container In a cool dry place	Hard Drying: 6 hours @ 30° C
Wet Film Thickness	2000-3000 μ	
Dry Film Thickness	1000-1500 μ per each coat	
Theoretical Coverage	0.5-1.0 m2/L per each coat	
	Spreading rate depends on applied film thickness, surface imperfections, type of surface texture, porosity of the substrate, environment temperature and wastage during application. Maximum spread rate per coat is obtained at minimum dry film thickness and vice versa.	NA
Surface Dry	1 hour at 30° C	
Over Coat	6 hours	
Hard dry	6 hours at 30° C	
<b>Surface Preparation</b>	The surface to be coated should be clean, non-chalky, dry and free from loose material, dust etc. In case of need sanding required to remove loose particles from the surface.	25 KG
<b>Recommended Coating System</b>	Stir the contents well before use. Do not apply the paint in very cold conditions, to impervious surfaces or surfaces subject to steam and condensation. It is advisable to build up coat thickness by applying in thin layers, instead of applying one single thick coat to avoid cracking. Avoid painting below 10° C and humidity more than 85% .	 Non-Flammable

<b><u>Exterior</u></b>  Primer Top Coat	1 X Oscar Original Sealer 5290(Optional) 1 X Oscar Atique 5355	
<b><u>Interior</u></b>  Primer Top Coat	1 X Oscar Beauty Sealer 5292(optional) 1 X Oscar Atique 5355	Paint System
<b><u>Repainting System</u></b>  Substrate Primer Top Coat	For repainting & fresh substrate same procedure as below  Any smooth existing surfaces 1 X Oscar Original Sealer 5290/Oscar Beauty Sealer 5292 1 X Oscar Atique 5355	
<b><u>Application Data</u></b>	Application by Hand and Trowell  Add the hay with Atique base and mix it properly. Apply it using the hand and trowel to get a particular pattern or finish. The hay and application using hand creates the heritage antique effect on wall.	Splashes on eye-wash with Water
<b>Health and Safety</b>	Ensure good ventilation during application and drying.  Avoid contact of the product with skin and eyes by using proper gloves, apron , goggles and mask.  If splashes enter eyes wash with plenty of water.  Keep out of reach of children.  Remove splashes from skin with soap and warm water. In case of insufficient ventilation during spraying, wear suitable respiratory equipment. Do not breathe vapour / spray.	
<b>DISCLAIMER</b>	The above information is based on internal testing and our accumulated experience. This information is given in good faith but without warranty as the conditions under which the product is used are often beyond our control. This data sheet supersedes those previously issued and may be changed without prior notice.	